

**E MOTORS****JIANGSU E MOTORS CO.,LTD.**

TEL: +86 519 8622 3308-8029

FAX: +86 519 8622 3308-8032

EMAIL: emotorspower@emotorsgroup.com

Website: www.emotorsgroup.com

ADD: 86 Wujin Boulevard West, Wujian Industrial Zone, Chagnzhou city, Jiangsu Province, China.

## 48V10Ah Telecom Sector Spec.

Material	LiFeP04
System Item	48V10AH
Standard Voltage (V)	48
Capacity (C/5) (AH)	10
Output Energy (C/5) (WH)	480
Structure Size	
Width (mm)	483 (19" )
Hight (mm)	45 (1U)
Depth (mm)	350
Weight (kg)	9
Electrical Parameters	
Electric Window (V)	40~56.5
Charge Voltage (V)	56.5
Charge Mode	0.5C
Max Continul Discharge Current (A)	10
Charge time (h)	2.5h to 100%
Different electric time discharge power	
30min (W)	1000
1h (W)	500
2h (W)	250
4h (W)	120
Working Condition	
lifespan +25℃	>10year
Working Temprature	-20℃~+60℃
Conventional Transport	UN3480
Storage temperature and duration	1 year@20℃ 6 months@30℃ 3 months@40℃
Electromagnetic compatibility standard	EN61000 chapter4.2,4.3,4.4,4.5,4.6/EN55022
Safety Certification	CE,TLC, Justifiable GR1089 & GR63 design
Safety Standard	IEC60950/UL1642/UL2054
IP Grade	IP20